

# FLECK 5812 CONTROL VALVE

HIGH PERFORMANCE FLEXIBLE 1-1/4" VALVE

**MADE IN THE  
USA**  
OF FOREIGN & DOMESTIC PARTS



## FEATURES/BENEFITS

Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant

Continuous service flow rate of 43 GPM with a backwash of 33 GPM

Backwash capability accommodates softener tanks up to 24" and filters up to 24" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Time-tested, hydraulically-balanced piston for service and regeneration

Optical sensor for precision cycle positioning

Soft water refill for a cleaner brine tank

Designed with double backwash for reduced hardness leakage

Diagnostics for historical valve performance

Programming stored in memory and will not be lost due to power outages

## OPTIONS

Filter or softener control valves

Downflow co-current or upflow counter-current regeneration

Plumbing connections in 3/4", 1" or 1-1/4" NPT, BSP, sweat, and CPVC

Fiber-reinforced polymer high-flow bypass valve

Variable reserve for increased efficiency

Programmable regeneration types for increased flexibility

Three color bezel options of black, blue, or silver

**XTR2-** Premium touch screen LCD display with two programmable relay outputs for both normally opened and normally closed contacts

**SXT-** Large LCD display with one programmable relay output for both normally open and normally closed contacts



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 44 for Water Softener Performance.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.



UL recognized to the 979



TESTED EMC and Low Voltage Directive



Restriction of Hazardous Substance Compliant

## VALVE SPECIFICATIONS

Valve Material	Fiber-reinforced polymer
Inlet/Outlet	3/4", 1", or 1-1/4" NPT/ BSP/Sweat/CPVC
Cycles	5

## FLOW RATES (50 PSI INLET) – VALVE ALONE - 2.5" BASE

Piston	Downflow	Upflow	Filter
Continuous (15 psi drop)	43 GPM 9.9 m <sup>3</sup> /hr	39 GPM 8.9 m <sup>3</sup> /hr	37 GPM 8.4 m <sup>3</sup> /hr
Peak (25 psi drop)	56 GPM 12.7 m <sup>3</sup> /hr	51 GPM 11.9 m <sup>3</sup> /hr	47 GPM 10.7 m <sup>3</sup> /hr
Cv (flow at 1 psi drop)	11.2	10.1	9.4
Max. Backwash (25 psi drop)	33 GPM 7.5 m <sup>3</sup> /hr	36 GPM 8.1 m <sup>3</sup> /hr	45 GPM 9.9 m <sup>3</sup> /hr

## FLOW RATES (50 PSI INLET) – VALVE ALONE - 4" BASE

Piston	Downflow	Upflow	Filter
Continuous (15 psi drop)	45 GPM 10.3 m <sup>3</sup> /hr	40 GPM 9.1 m <sup>3</sup> /hr	38 GPM 8.7 m <sup>3</sup> /hr
Peak (25 psi drop)	59 GPM 13.3 m <sup>3</sup> /hr	52 GPM 11.7 m <sup>3</sup> /hr	50 GPM 11.3 m <sup>3</sup> /hr
Cv (flow at 1 psi drop)	11.7	10.3	9.9
Max. Backwash (25 psi drop)	34 GPM 7.8 m <sup>3</sup> /hr	36 GPM 8.2 m <sup>3</sup> /hr	45 GPM 10.2 m <sup>3</sup> /hr

## REGENERATION

Downflow/Upflow	Both
Adjustable Cycles	Yes
Time Available	
SXT:	0 - 199 min/cycle
XTR2:	0 - 240 min/cycle

## METER INFORMATION

Meter Accuracy	
1-1/4" Turbine:	2 - 40 GPM ± 5% (0.45 - 9 m <sup>3</sup> /h)
Meter Capacity Range	
SXT:	1 - 999,900 gal (0 - 3,785 m <sup>3</sup> )
XTR2:	1 - 9,999,999 gal (0 - 378,541 m <sup>3</sup> )

## DIMENSIONS

Distributor Pilot	1.05" O.D. (26.7 mm) 32 mm O.D. 1.315" O.D. (33.4 mm) 1.9" O.D. (48.3 mm)
Drain Line	1.5" NPT Quick-Connect
Brine Valve 1600:	3/8" or 1/2"
Injector System	1610
Mounting Base	2.5" – 8 NPSM 4" – NPSM
Height from Top of Tank	12" (305 mm)
Riser Height	1/4" Below top of tank

## TYPICAL APPLICATIONS

Water Softener	8 - 24" diameter
Filters	8 - 24" diameter based on 10 GPM/ft <sup>2</sup>

## ADDITIONAL INFORMATION

Electrical Rating	12 Volts DC
Estimated Shipping Weight	12 lbs
Pressure	
Hydrostatic:	300 psi (20 bar)
Working:	20 - 125 psi (1.4 - 8.5 bar)
Temperature	
Cold Water Valve:	34 - 110°F (1 - 43°C)



5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | F: 262.238.4404

WATERPURIFICATION.PENTAIR.COM

CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

© 2017 Pentair Residential Filtration, LLC. All rights reserved.

§For a detailed list of where Pentair trademarks are registered, please visit [waterpurification.pentair.com/brands](http://waterpurification.pentair.com/brands). Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

4004319 REV D JL17